

# Kenseal-100™



General-Purpose Acrylic Sealant

## PRODUCT DESCRIPTION

**Kenseal-100™** is a flexible, general-purpose acrylic latex sealant used for interior and exterior caulking in architectural applications where joint movement can occur. Its elastomeric properties make it an excellent sealant for air-conditioner ducting systems, building services, and aluminium window and door frames as a complete system. It is ideal for caulking floor planks, hollow-core ceiling, plywood sidings, gypsum boards and baseboards. It may also be used to grout marble and ceramic tiles, repair mortars, concrete joints and seal wall cracks.



SIZE 300 mL

**British Standard 476, Part 6 & 7**  
— CERTIFIED —

## APPLICATION

- Surface must be clean and dry before applying – no dust, oil and grease
- No primer required for aluminium, air-con ducting and most porous surfaces
- Use primer for non-porous surfaces if necessary
- Smooth sealant using a slightly-wetted stick, spatula or finger

## TECHNICAL DATA

- **Raw material base:** Acrylic Resin Dispersion
- **Skin formation time:** approx. 20 min at 23°C/50% rel. humidity
- **Curing speed:** approx. 2 mm after 24 hours at 23°C/50% rel. humidity
- **Application temperature:** -25°C to 85°C
- **Paintability:** excellent after curing
- **Density:** 1.6g/cm<sup>3</sup>
- **Elongation:** approx. 50%
- **Shelf life:** at least 24 months when stored in a cool, dry place
- Non-flammable, non-toxic, non-irritating, and environment-safe



THE HVAC MATERIAL SPECIALIST

**Kenmech (Asia) Marketing Pte Ltd**

T: (65) 6743 2788 F: (65) 6745 7339 M: (65) 9669 9959  
E: Asia.Kenmech@gmail.com  
www.Kenmech.com.sg  
Blk 1031, Eunos Avenue 6, #01-49  
Singapore 409626

*Disclaimer: The information contained in this document is believed to be accurate at the date of publication. KENMECH does not accept responsibility for the results of using the product in applications different from those described above.*

